



**Model** RG 13 Series II

**Weight** 262 lb (119 kg)

**Width** 25" (63.5 cm)

**Ground Drive** Push type

**Engine** Honda 13 hp (9.7 kW)

**Fuel Tank** 1.72 gal (6.5 L)

**Cutter Wheel** 11" x .375" (27.9 cm x .953 cm)

**Super Tooth®** 8 total

**Clutch** Centrifugal

**Cutting Depth** 13" (33 cm)

**Cutting Height** 22" (55.9 cm)

**Standard Features** Adjustable Handle Bars  
Operators Presence Safety Bar



**Model** RG 13

**Weight** 420 lb (191 kg)

**Width** 31" (78.7 cm)

**Ground Drive** Push type

**Engine** Honda 13 hp (9.7 kW)

**Fuel Tank** 1.72 gal (6.5 L)

**Cutter Wheel** 14" x .375" (35.6 cm x .953 cm)

**Super Tooth®** 12 total

**Clutch** Direct drive

**Cutting Depth** 18" (45.7 cm)

**Cutting Height** 20" (50.8 cm)

**Standard Features** Adjustable Handle Bars  
Operators Presence Safety Bar  
Electric Start 4



**Model** RG 25HD

**Weight** 583 lb (264 kg)

**Width** 29" (73.7 cm)

**Ground Drive** Self-propelled, hydrostatic variable speed

**Engine** Kohler Command 25 hp (18.6 kW)

**Fuel Tank** 3 gal (11.4 L)

**Cutter Wheel** 14" x .375" (35.6 cm x .953 cm)

**Super Tooth®** 12 total

**Clutch** Electromagnetic

**Cutting Depth** 22" (55.9 cm)

**Cutting Height** 24" (61 cm)

**Standard Features** Adjustable Handle Bars  
Operators Presence Safety Bar  
Electric Start  
Self-Propelled



All start up functions are done at the operators station keeping the operator a safe distance form the cutter wheel.



Handle bar is height adjustable and equipped with an operator presence safety shut-down bar.